

Technical Specifications

FSOC(Fusion Splice On Connector) LC 0.9mm

Connector type	Fiber type	Boot	Sleeve	Cable
LC/APC & LC/UPC	SM & MM	Soft Boot	25mm	0.9mm Dia.

1. General

This technical specification describes the information of the components and the characteristics of UCL's Fusion Splice-On Connector, LC type with SM and MM fiber, 0.9mm buffered jacket cable that is terminated on the UCL's All-In-One Fusion Splicer, KF4A and K33A.

2. Features and Benefits

- Fusion technology shows better optical performance and reliability versus mechanical splice connector
- Eliminate cable shorts and excess slack, just in length installation
- Easy and Fast installation with KF4A & K33A, All-In-One fusion splicer

3. Specifications


3.1 Optical Performance

Singlemode (OS1 & OS2)	Insertion Loss	Typ.	0.15dB
		Max	0.30dB
	Return Loss	min.	55dB (UPC), 65dB (APC)
Multimode (OM1,OM2,OM3 & OM4)	Insertion Loss	Typ.	0.10dB
		Max	0.20dB
	Return Loss	min.	30dB

3.2 Standards Compliance

Intermateability	IEC 61754-20, TIA/EIA-604-10
Endface	IEC 61300-3-35
Geometry	GR-326-CORE, 4.4.5 Geometry Requirements
Reliability	TIA-568-C.3 (3rd party certification)
Material	RoHS, UL94V-0

4. Dimension



5. Ordering Information

Part Number	Product Description	Length (mm)
FSOC-D0-LC/APC-25-SB-09A	G.652.D, LC type, APC polishing, 25mm sleeve, 0.9mm soft boot	55
FSOC-D0/P-LC/APC-25-SB-09A	G.652.D, Pre-cleaved, LC type, APC polishing, 25mm sleeve, 0.9mm soft boot	55
FSOC-A2-LC/APC-25-SB-09A	G.652.A2, LC type, APC polishing, 25mm sleeve, 0.9mm soft boot	55
FSOC-A2/P-LC/APC-25-SB-09A	G.652.A2, Pre-cleaved, LC type, APC polishing, 25mm sleeve, 0.9mm soft boot	55
FSOC-M4-LC/UPC-25-SB-09A	OM4, LC type, UPC polishing, 25mm sleeve, 0.9mm soft boot	55
FSOC-M4/P-LC/UPC-25-SB-09A	OM4, Pre-cleaved, LC type, UPC polishing, 25mm sleeve, 0.9mm soft boot	55

6. Splicing & Heating Condition on KF4A and KF4

Mode	Condition
Splicing Mode	12. G657A2B2, 1. SM ITU-T G652
Heating Mode	Temp. : 170~190 Deg. Time : 40~60sec

7. Related Products

Classification	Product Number	Product Description
Fusion Splicer	KF4, KF4A	UCL Fusion Splicer, Cladding Splicer
Fusion Splicer	K33, K33A	UCL Fusion Splicer, Core Splicer
FSOC Holder	HF4-ILC	FSOC-LC Holder, Right on KF4, KF4A
FSOC Holder	HS-ILC	FSOC-LC Holder, Right on K33, K33A
Cable Holder	HS-900	Cable Holder for 900um tight buffered cable, Left
Cable Holder	LS-900	Cable Holder for 900um loosed tube cable, Left



8. Documents

Document Number	Description
IG-FSOC-LC09SB-A-001	Installation Manual
RT-TI-FSOC-ST09SB-A-001	Reliability Test Report (TIA-568-C.3)